

IMPORTANT

READ ALL INSTRUCTIONS BEFORE STARTING

PREPARING THE SURFACE

- Park the vehicle in the shade or out of the sun.
- Wash surface thoroughly using a high-quality carwash soap of your preference.

Note: *Professional Detailers: Decontaminate and correct paint using the appropriate compound and pad. Thoroughly clean compound from all surfaces prior to application of Rapid Ceramic Paint Sealant. Keep in mind this product is very durable and will seal in any imperfections.*

- Thoroughly dry vehicle and ensure all surfaces are cool to the touch before application.

RAPID CERAMIC PAINT SEALANT APPLICATION

Note:

- *Complete the following steps on each panel of the vehicle before moving on to the next. This will ensure you have adequate time to achieve incredible results.*
- Gently shake bottle for approximately 10 seconds.
- Evenly spray a light coat directly to the surface. Using one side of the towel, wipe the coating evenly across the surface.
- Immediately flip the towel to a clean dry side and buff the coating to an incredible shine. Inspect each section after buffing to ensure no haze remains. If any haze is present, buff the haze away to a high gloss shine.
- Cerakote Rapid Ceramic Paint Sealant will cure for approximately 2 hours. During this time, you will notice the gloss level and slickness increase dramatically.
- **IMPORTANT!** Do not expose to moisture during the 2-hour cure.

Congratulations!

You Have Achieved Sealed in Protection with Maximum Gloss & Shine!

TIPS & FAQ's

- Can I reapply? Yes, multiple layers will improve performance attributes. Cerakote Rapid Ceramic Paint Sealant can be reapplied at any time to a clean dry surface.
- I missed a spot and can see haze: If the coating has cured for more than two hours, simply reapply the Rapid Ceramic to the hazy area and buff to a shine.



LOVE IT? LET US KNOW BY POSTING
YOUR REVIEW & PHOTOS ONLINE.

RAPID CERAMIC PAINT SEALANT APPLICATION INSTRUCTIONS

WE STRONGLY RECOMMEND WATCHING THE INSTRUCTIONAL
VIDEO, WHICH SHOWS THIS PROCESS VISUALLY

SCAN WITH YOUR PHONE
FOR A HELPFUL
INSTRUCTIONAL VIDEO



cerakoteceramics.com/pages/paint-sealant-instructions



We're here to help. Give us a call at **866.774.7628** or email us at technicalsupport@cerakoteceramics.com

V10072022